

VELOCIFERO CITY X 125

TECHNICAL SPECIFICATIONS



Big wheels. Distinctive city style.

The City X 125 combines a liquid-cooled four-valve engine with electronic fuel injection and 16-inch wheels. A five-inch TFT display, twin hydraulic rear shock absorbers and a 7.8-litre fuel tank complement its distinctive urban design.

125 cc

LIQUID-COOLED ENGINE

10.8 kW

AT 8,250 RPM

790 mm

SEAT HEIGHT

ENGINE & PERFORMANCE

Engine	125 cc, four-stroke single-cylinder, 4 valves
Cooling	Liquid-cooled
Maximum power	10.8 kW at 8,250 rpm
Maximum torque	12 Nm at 6,500 rpm
Fuel system	Electronic fuel injection (EFI)
Ignition	ECU
Compression ratio	12:1
Maximum speed	100 km/h

DIMENSIONS & CAPACITY

Length x width x height	1,960 x 735 x 1,150 mm
Wheelbase	1,360 mm
Seat height	790 mm
Ground clearance	146 mm
Weight in running order	136 kg
Fuel tank	7.8 litres

CHASSIS, SUSPENSION & TYRES

Frame	High-tensile steel
Front suspension	Telescopic hydraulic fork
Rear suspension	Twin hydraulic shock absorbers
Front tyre	100/80-16
Rear tyre	120/80-16

INSTRUMENTS & EMISSIONS

Instruments	5-inch TFT display
Emissions standard	Euro 5+